


specifications

SKT1000-A Series

Top Mount ActiveCore
Dixell XR75CH Controller



Copyright © 2018 SKOPE Industries Limited

GENERAL SPECIFICATIONS	
Temperature range	1°C to 4°C (adjustable up to 15°C)
Climate class	5 (tested at 43°C)
Doors	Lockable, self-closing, double-glazed, single low-e, argon-filled, toughened safety glass swing doors (hinged left hand, right hand)
Internal volume	897 L
Shelves	10 adjustable height wire shelves: 500 mm wide x 470 mm deep (5 each door)
Power supply	220-240 volts a.c. 50 Hz, single phase supply. Supplied with a 10 amp 3-pin plug
Current draw	4.0 amps (includes unit 2.9 amps)
Refrigeration system	Removable ActiveCore top mount refrigeration unit (UTSCCI-0016) (compressor Embraco FF112HBK)
Refrigerant	R134a/380 g
Nominal capacity	836 watts
Controller	Dixell XR75CH
Connectivity interface	ModbusRTU
Drainage	No plumbing required
Weight	225 kg

INDIVIDUAL SPECIFICATIONS			
Model ID	SKT1000Z-A	SKT1000Z-AC	SKT1000Z-ACX
SKOPE ID	MTZ10GY	MTZ10BY	MTZ10BX
Sign	Sign replacement panel	400 mm high illuminated sign	
Sign lighting	n.a.	1 x 17W T8 LED tube (Ø26 mm x 1034 mm)	
Interior side lights	2 x 20W (1400 mm) LED module strip side lights (all models)		
Interior shelf lights	n.a.	n.a.	10 x 7 W LED module strip shelf lights

SKOPE Industries Limited reserve the right to alter specifications without notice.

PSS0543 | Rev. 1.1 Apr. 2024