


FRONT VIEW




SIDE VIEW




REAR VIEW





TOP VIEW



GENERAL CHARACTERISTICS		
Number of trays 600 × 400 mm (H= 40 mm)	-	240
Number of trays 600 × 800 mm (H= 40 mm)	-	120
Effective internal Cell volume UNI EN 16825	dm^3	2145,6
Number of compartments	-	3
Category		Vertical
Working temperature		Multipurpose: frozen and chilled food
IRINOX Spa, Via Madonna di Loreto 6/B 31020 Corbanese di Tarzo (TV) Italy		

HEIGHT			
Standard feet	mm	2560	115 ÷ 165
Lowered feet option	mm	2530	85 ÷ 115
Raised option	mm	-	- ÷ -
Wheel option	mm	2600	155

Compatible condensing units: C512

Measurement in millimeters

IRINOX

Mod.: **CP 120**

Cod.: **PCP120MxCOxxxx**

Ed.: **01/08/2018** Rev.: **00**

CABINET ONLY (CO)						
Electric supply:	-	230V-1N+PE 50Hz	230V-1N+PE 60Hz	-	-	-
Total rating (FLI)	kW	3,90	3,90	-	-	- / -
Full load amps (FLA)	A	16,50	16,50	-	-	- / -
Main power cable	mm^2	3 × 3G2.5	3 × 3G2.5	-	-	-
Refrigerant type:	-	R404A / R452A				
Liquid Line Connection	øIn (ømm)	3/8" (9.53 mm)				
Suction line connection	øIn (ømm)	5/8" (15.88 mm)				
Hot gas line connection	øIn (ømm)	3/8" (9.53 mm)				
Maximum ambient air temperature:	°C	42				

Standard packing		
Gross Weight	kg	825
Dimensions (W × D × H)	mm	1000 × 1300 × 2500 × № 3
Volume	m^3	10,50

Compatible condensing units: C512

Measurement in millimeters

IRINOX

Mod.: **CP 120**

Cod.: **PCP120MxCOxxxx**

Ed.: **01/08/2018** Rev.: **00**